

## 锻钢蜗轮传动球阀 FORGED STEEL WORM GEAR BALL VALVE



# BALL VALVE





### 设计特点

防火设计 低泄漏控制 双向阻塞及泄放功能

## 制造范围

尺寸范围: 2"~48" 压力等级: ANSI 150LB-2500LB

#### 操作性能

阀体材料:碳钢、不锈钢 内件材料:软密封、金属密封 操作方式:手动、齿轮、电动、气动、液动

#### Design Features

Fire protection design
Low leakage control
Bidirectional blocking and discharging function
Pressure in the chamber from the discharge function overload

#### Manufacturing Scope

Diameter: 2"~48" Pressure: ANSI 150LB~2500LB

#### Operating Performance

Body Material: Carbon Steel Stainless Steel
Trim Material: Soft sealing, Metal seal
Mode of operation:
Manual operation, gear, electric, pneumatic, hydraulic





十 管线球阀 — Line ball valve ── 双向硬密封蜗轮传动偏心半球阀 ── Two - way Hard - sealed Worm Gear Eccentric Semi - ball Valve

<b>可生产阀门类型</b> Type of valve	软密封球阀、固定硬密封球阀、三通四通换向球阀、全焊接球阀、真空球阀、上装式球阀、偏心半球阀等 Floating ball valve, trunnion mounted metal seat ball valve, 3way/4\vay ball valve, fully-welded ball valve, vacuum ball valve, topentry ball valve, Eccentric Ball Valve, etc.
可按各类标准生产	机械部标准、化工部标推、美标、日标、德标及其它非标。
Standard of product	JB, HG, ANSI, DIN, and other non-standard.
可生产的尺寸范围	DN15~DN1200(不同阀门类型尺寸范围有所不同,详情请电询)
Size range	2"~56" (different valve type, different size, please call for details)
可生产的压力范围	PN16~PN420(不同阀门类型压力范围有所不同,详情请电询)
Pressure range	Class 150Lb~Class2500Lb (different valve type, different pressure, please call for details)
可常用供应的阀体材料	碳钢、不锈钢、合金钢、蒙乃尔、特种钢等。
Material of body	Carbon steel, stainless steel, alloy steel, monel alloy, special steel etc.
可常用供应的内件材料	按适用介质选材
Material of rim	According to the medium

详细连接尺寸,或者索要总装图,请电询公司销售部门。 More details, pls contact our sales department.



→ 双向硬密封电动上装式偏心半球阀 —
Two - Way Hard - Sealed Electric Mounted Eccentric Half - Ball Valve





Breakthrough technology The future of the valve



→ 手柄浮动球阀 — Handle floating ball valve



- 锻钢三片式法兰球阀
 Forged steel three - piece flange ball valve







── 蜗轮传动球阀 ── Worm Gear Ball Valves



十 卸灰球阀 ——— Unloading ball valve



